



UML is not enough...




- Possible number of owners a car can have
- Required age of car owners
- Requirement that a person may own at most one black car

Some OCL examples I



“A vehicle owner must be at least 18 years old”:

Some OCL examples I




“A vehicle owner must be at least 18 years old”:

context **Vehicle**

inv: **self. owner. age >= 18**


Some OCL examples I



“A vehicle owner must be at least 18 years old”:

context **Vehicle**
inv: **self. owner. age** \geq 18

Some OCL examples I




“A vehicle owner must be at least 18 years old”:

context **Vehicle**

inv: **self. owner. age >= 18**

Some OCL examples I




“A vehicle owner must be at least 18 years old”:

context **Vehicle**

inv: **self. owner. age >= 18**

Some OCL examples I




“A vehicle owner must be at least 18 years old”:

context **Vehicle**

inv: **self. owner. age >= 18**

Some OCL examples I



“A vehicle owner must be at least 18 years old”:

context Vehicle


inv: self.owner.age \geq 18

What does this mean, instead?

context Person

inv: self.age \geq 18

Some OCL examples I



“A vehicle owner must be at least 18 years old”:

context Vehicle


inv: self.owner.age \geq 18

“A **car** owner must be at least 18 years old”:

context Car


inv: self.owner.age \geq 18

Some OCL examples II



“Nobody has more than 3 vehicles”:

Some OCL examples II




“Nobody has more than 3 vehicles”:

context Person
inv: self.fleet->size <= 3


or change multiplicity

Some OCL examples II



“All cars of a person are black”:

Some OCL examples II




“All cars of a person are black”:

context Person

inv: self.fleet->forAll(v | v.colour = #black)

Some OCL examples II




“All cars of a person are black”:

context Person

inv: self.fleet->forAll(v | v.colour = #black)

“Nobody has more than 3 black vehicles”:

Some OCL examples II




“All cars of a person are black”:

context Person
inv: self.fleet->forAll(v | v.colour = #black)

“Nobody has more than 3 black vehicles”:

context Person
inv: self.fleet->select(v | v.colour = #black)->size <= 3

Some OCL examples III — iterate




What does this mean?

context Person

inv: self.fleet->iterate(v; acc:Integer=0
| if (v.colour=#black)
then acc + 1 else acc endif) <=3


Some OCL examples IV — oclIsKindOf



context Person

inv: age < 18 implies self.fleet->forAll(v | not v.ocllsKindOf(Car))

Some OCL examples IV — oclIsKindOf




context Person

inv: age < 18 implies self.fleet->forAll(v | not v.oclIsKindOf(Car))

“A person younger than 18 owns no cars.”

Some OCL examples IV — oclIsKindOf




context Person

inv: age<18 implies self.fleet→forAll(v | not v.ocllsKindOf(Car))

“A person younger than 18 owns no cars.”

“self” can be omitted.

Some OCL examples IV — oclIsKindOf



context Person


inv: age < 18 implies self.fleet → forAll(v | not v.ocllsKindOf(Car))

“A person younger than 18 owns no cars.”

“self” can be omitted.

Logical Junctors: and, or, not, implies, if...then...else...endif, =


Some OCL examples V — allInstances



context Car

inv: Car.allInstances()->exists(c | c.colour=#red)

Some OCL examples V — allInstances




context Car

inv: Car.allInstances()->exists(c | c.colour=#red)


“There is a red car.”

OCL pre-/post conditions — Examples



So far only considered class invariants.


OCL pre-/post conditions — Examples



So far only considered class invariants.

OCL can also specify operations:

OCL pre-/post conditions — Examples



So far only considered class invariants.

OCL can also specify operations:


“If `setAge(...)` is called with a non-negative argument then the argument becomes the new value of the attribute `age`.”

context `Person::setAge(newAge:int)`

pre: `newAge >= 0`

post: `self.age = newAge`

OCL pre-/post conditions — Examples




So far only considered class invariants.

OCL can also specify operations:

“Calling birthday() increments the age of a person by 1.”

context Person::birthday()
post: self.age = self.age@pre + 1

OCL pre-/post conditions — Examples



So far only considered class invariants.


OCL can also specify operations:

“Calling getName() delivers the value of the attribute name.”

context Person::getName()

post: result = name


Queries



Special to OCL are operations with a `«query»` stereotype:

Only these operations can be used within an OCL expression.

Queries



Special to OCL are operations with a `«query»` stereotype:

Only these operations can be used within an OCL expression.

“Calling `getName()` delivers the value of the attribute name.”

context Person

inv: `self.getName() = name`